



Front ITO Film-0.188mm
 Back ITO Glass-1.8mm

Thick: 2.3±0.15

- Notes:
- Type: Film to Glass
 - Operating Voltage: ≤10v
 - Operation Temperature: -20°C ~ 65°C
Storage Temperature: -30°C ~ 70°C
 - Life Time: 1,000,000 times
 - Connect Material: FPC
 - Response Time: ≤10ms
 - Linearity: ≤1.5%
 - Transmittance: ≥75%
 - Surface Hardness: ≥3H (pencil)
 - Operation force: 60g ~ 150g

- Resistance: 50Ω < PIN1, PIN2 < 250Ω
50Ω < PIN2, PIN4 < 250Ω
50Ω < PIN4, PIN5 < 250Ω
50Ω < PIN5, PIN1 < 250Ω

TOLERANCES
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES
>2000MM	±2.00MM
1600< X ≤2000MM	±1.20MM
1200< X ≤1600MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM

格林触控
GreenTouch® GreenTouch Technology Co.,Ltd

Model No.:	GT-5W-15.6C-1	Size	15.6"	Ratio	16:9
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2016.6.3	Page	1/1
Check	付作书	Date	2016.6.3	Version	A0
Release	汪燕	Date	2016.6.3		